VIENNA CALEO COLD DISPLAY

MODEL # VIAS-34-R-SL-SC-INS-CAL

SPECIFICATIONS

The Vienna Caleo series Cold Display is a slanted lower profile air screen with built-in hot gas condensate evaporation system (self-contained), so a floor drain is not required. This unit features (2) glass shelves, LED lighting and a pull-down night shade. This unit is offered in several sizes and designed for a variety of applications; back-to-back, wall mounted, front line or as part of an island merchandiser with other Caleo models.

A '1			
Available lengths: ☐ 23 5/8"	☐ 31 1/2"	☐ 47 1/4"	
Available depths: 26"			
Available heights: ☐ 55 1/2"			



STANDARD FEATURES

- Self-contained refrigeration
- Stainless steel exterior
- Stainless steel perforated rear interior
- Slanted glass profile
- Insulated glass end
- (2) tempered glass shelves
- LED lighting
- Front air dam glass
- Removable stainless deck pans for cleaning
- Air cooled system with variable speed fan
- Lift-up evaporator
- Programmable digital refrigeration controller
- Front air intake
- Air discharge through rear ducts
- Manual pull-down night curtain
- Adjustable feet & casters
- Hot gas evaporation system (self-contained only)
- 5-year compressor warranty
- ETL listed in accordance with UL 471 & NSF 7 standards

OPTIONAL FEATURES

- □ Remote Refrigeration (Floor Drain Required)
- □ Powder Coat Exterior Finish
- □ Front Breathing Kit (on VIAS3 only)
- □ Rear Air Duct (for back to back or wall units)
- □ Full Flex Series Panels
- □ Flex Series Panel Finish Options
 - □ Laminate
 - □ #4 Brushed Stainless Steel
 - □ #8 Mirror Polished Stainless
 - □ Wood Veneer



Conforms to UL Standard 471, and NSF Standard 7; Certified To CSA Standard C22.2 No.120 DOE 2017 Energy Efficiency Compliant

SELF CONTAINED	L	D	н	HP	VOLT	AMPS	PLUG	WT	REFRIG.
VIAS1-34-R-SL-SC-INS-CAL	23 5/8	26	55 1/2	1/2	115V	9.5	5-15P	345	R452A
VIAS2-34-R-SL-SC-INS-CAL	31 1/2	26	55 1/2	1/2	115V	9.5	5-15P	437	R452A
VIAS3-34-R-SL-SC-INS-CAL	47 1/4	26	55 1/2	7/8	208-230V	7.7	L14-20P	530	R452A
REMOTE	L	D	н	вти	VOLT	AMPS	PLUG	WT	REFRIG.
VIAS1-34-R-SL-RR-INS-CAL	23 5/8	26	55 1/2	2701	115V	1.5	5-15P	305	R452A
VIAS1-34-R-SL-RR-INS-CAL VIAS2-34-R-SL-RR-INS-CAL	23 5/8 31 1/2	26 26	55 1/2 55 1/2	2701 3189	115V 115V	1.5 1.7	5-15P 5-15P	305 397	R452A R452A


CALL TOLL FREE: 800-525-3692 (609-714-2330) FAX: 609-714-2331 www.rpiindustries.com 220 ROUTE 70, MEDFORD, NJ 08055





PROJECT:


TOLL FREE: 800-525-3692


MODEL # VIAS-34-R-SL-SC-INS-CAL


















Click the below links to access KCL / Revit files VIAS1-34 VIAS2-34 VIAS3-34

VIAS1-34-R-SL-SC-INS-CAL

VIAS2-34-R-SL-SC-INS-CAL

VIAS3-34-R-SL-SC-INS-CAL



4" clearance is required for back to back units or if going up against a wall. Rear air duct will be provided by factory at no extra charge upon request. Please specify if air duct will be required when ordering.

(Exhaust air duct is required for wall installation)

- 1. Ventilation louvers, MUST be provided in the cabinet or counter and located so to provide full ventilation for the condensing unit.
- 2. The VIAS-CAL merchandiser is designed for use in locations where temperatures and humidity do not exceed 75 degrees and 55% R.H. Locate away form direct sunlight, rapid air currents and extreme temperature changes. Exposure to air currents from ceiling fans, air conditioners, ovens, etc. will disrupt the cases air current and refrigeration zone within. Any adverse field conditions stated above will void warranty.

RPI in line with it's policy to continually improve it's product reserves the right to change materials and specifications without notice.

CALL TOLL FREE: 800-525-3692 (609-714-2330) FAX: 609-714-2331 www.rpiindustries.com 220 ROUTE 70, MEDFORD, NJ 08055

